



Chimney Surrounds

Chimney Surrounds

A great way to top off your new design is to shield the chimney cowl with a Spectrum aluminium chimney surround. Standard designs include open or louvre enclosed frames that are available in a wide range of popular powder coat colours. Enclosed frames offer a choice of airfoil or rectangular slat infills, and spacing and orientation can often be adjusted to suit your design.

Features

- Configurable design - select louvre spacing from 65mm or 100mm, or frame only design
- Framed Single bay up to 2.2m long, double bay up to 4.4m long
- Louvred Single bay up to 1.9m long, double bay up to 3.8m long
- Tough powdercoated finish in your choice of colour*
- Available to suit sheet, weatherboard, or brick substrates
- Designed and made in New Zealand

Louvred Surround
65mm (Centres)



Louvred Surround
100mm (Centres)



Framed Surround



- SURFACE FINISH - Powdercoated (Dulux Duralloy or Duratec range) or anodised (*)
- MATERIALS - 6060 T5/T6 aluminium - 316 Stainless steel
- NZBC COMPLIANCE - B1 (Structure), B2 (Durability)
- COMPLIANCE SPECIFICATION - Maximum wind speed = 55 m/s (Extra high wind zone)
- INSTALLATION - Spectrum Balustrade Systems to be fully installed by accredited installers